

WEBTROL

There when you need us most



Wastewater Pumps & Accessories

- Effluent Pumps • Sewage Pumps • Grinder Pumps
- Engineered Grinder Pumps and Non-clogs • Accessories

webtrol.com



There when you need us most

VE3A30A EFFLUENT SUMP PUMPS


1/3 HP Stainless Steel/Cast Iron/Thermoplastic Sump Pumps

VE Series

Features and Benefits

- Designed for light residential effluent
- Versatile for many drainage & dewatering applications
- Automatic operation
- Recessed vortex impeller to ensure flow of liquids as well as solids
- Continuous duty motor
- Maintenance-free design

**2 Year
Warranty**



Model	HP	Volt	Discharge	Cord Length	Solid Passage	Dimensions (L x W x H)	Weight
VE3A30A	.3	115	1.5"	10'	.5"	8.9" x 5.7" x 11.1"	18 lbs.

VE5A46 EFFLUENT PUMPS


1/2 HP Stainless Steel/Cast Iron Effluent Pumps

VE Series

Features and Benefits

- Designed for residential effluent
- Versatile for many drainage & dewatering applications
- Recessed, cast iron, vortex impeller to ensure flow of liquids & solids
- Standard potted epoxy cord seals
- Double mechanical seal
- Continuous duty motor
- Maintenance-free design

**2 Year
Warranty**



Model	HP	Volt	Discharge	Cord Length	Solid Passage	Dimensions (L x W x H)	Weight
VE5A46	.5	115	2"	30'	.25"	8.7" x 5.7" x 14.7"	30 lbs.
VE5C46	.5	230	2"	30'	.25"	8.7" x 5.7" x 14.7"	30 lbs.



There when you need us most


VE5A55 EFFLUENT PUMPS

1/2 HP Stainless Steel/Cast Iron Effluent Pumps

VE Series

Features and Benefits

- Designed for residential effluent
- Versatile for many drainage & dewatering applications
- Recessed, cast iron, vortex impeller to ensure flow of liquids & solids
- Standard potted epoxy cord seals
- Double mechanical seal
- Continuous duty motor
- Maintenance-free design



Model	HP	Volt	Discharge	Cord Length	Solid Passage	Dimensions (L x W x H)	Weight
VE5A55	.5	115	2"	30'	.25"	12.9" x 6.8" x 17.8"	41 lbs.
VE5C55	.5	230	2"	30'	.25"	12.9" x 6.8" x 17.8"	41 lbs.

VE10C62 EFFLUENT PUMPS


1 HP Stainless Steel/Cast Iron Effluent Pumps

VE Series

Features and Benefits

- Designed for residential and commercial effluent
- Versatile for many drainage & dewatering applications
- Recessed, cast iron, vortex impeller to ensure flow of liquids & solids
- Standard potted epoxy cord seals
- Double mechanical seal
- Continuous duty motor
- Maintenance-free design

**2 Year
Warranty**



Model	HP	Volt	Discharge*	Cord Length	Solid Passage	Dimensions (L x W x H)	Weight
VE10C62	1	230	2"	30'	.25"	15.9" x 8.4" x 21.1"	75 lbs.
VE10C62-3	1	230-3ph	2"	30'	.25"	15.9" x 8.4" x 21.1"	75 lbs.
VE10D62-3	1	460-3ph	2"	30"	.25"	15.9" x 8.4" x 21.1"	75 lbs.

* 3" discharge available



There when you need us most

VE20C79-3 EFFLUENT PUMPS


2 HP - 3 Phase Stainless Steel/Cast Iron Effluent Pumps

VE Series

Features and Benefits

- Designed for residential and commercial effluent
- Versatile for many drainage & dewatering applications
- Recessed, cast iron, vortex impeller to ensure flow of liquids & solids
- Standard potted epoxy cord seals
- Double mechanical seal
- Continuous duty motor
- Maintenance-free design

**2 Year
Warranty**



Model	HP	Volt	Discharge*	Cord Length	Solid Passage	Dimensions (L x W x H)	Weight
VE20C79-3	2	230-3ph	2"	30'	.25"	15.7" x 8.4" x 21.9"	77 lbs.
VE20D79-3	2	460-3ph	2"	30'	.25"	15.7" x 8.4" x 21.9"	77 lbs.

* 3" discharge available



There when you need us most

WTE SERIES TURBINE EFFLUENT PUMPS

Stainless Steel Fitted Effluent Pumps

WTE Series

The WTE Series Turbine Effluent Pumps are specifically designed to handle the toughest effluent applications. These pumps are powered by .5 HP through 5 HP submersible motors.

The quality and performance you expect, along with industry best lead times and personalized service, only from Webtrol!



Features and Benefits

- Constructed from stainless steel and plastic
- Floating stack design to prevent clogging
- 240 inch SJOOW cable for demanding applications

Performance

HP Range: .5 to 5 HP, 60Hz

Capacities to 80 GPM

Heads to 840'

Temperatures to 85° F









Typical Services

- Residential
- Commercial
- Agricultural
- Municipal



There when you need us most

WTE SERIES TURBINE EFFLUENT PUMPS



VS5A24 SEWAGE PUMPS


1/2 HP Stainless Steel/Cast Iron Sewage Pumps

VS Series

Features and Benefits

- Designed for residential sewage
- Versatile for many solid handling & dewatering applications
- Recessed, cast iron, vortex impeller to ensure flow of liquids & solids
- Standard potted epoxy cord seals
- Double mechanical seal
- Continuous duty motor
- Maintenance-free design

**2 Year
Warranty**



Model	HP	Volt	Discharge	Cord Length	Solid Passage	Dimensions (L x W x H)	Weight
VS5A24	.5	115	2"	30'	2"	8.7" x 5.7" x 16.2"	30 lbs.
VS5C24	.5	230	2"	30'	2"	8.7" x 5.7" x 16.2"	30 lbs.

VS5A30 SEWAGE PUMPS


1/2 HP Stainless Steel/Cast Iron Sewage Pumps

VS Series

Features and Benefits

- Designed for residential sewage
- Versatile for many solid handling & dewatering applications
- Recessed, cast iron, vortex impeller to ensure flow of liquids & solids
- Standard potted epoxy cord seals
- Double mechanical seal
- Continuous duty motor
- Maintenance-free design

**2 Year
Warranty**



Model	HP	Volt	Discharge	Cord Length	Solid Passage	Dimensions (L x W x H)	Weight
VS5A30	.5	115	2"	30'	1.5"	8.7" x 5.7" x 16.2"	30 lbs.
VS5C30	.5	230	2"	30'	1.5"	8.7" x 5.7" x 16.2"	30 lbs.

VS5A38 SEWAGE PUMPS


1/2 HP Stainless Steel/Cast Iron Sewage Pumps

VS Series

Features and Benefits

- Designed for residential sewage
- Versatile for many solid handling & dewatering applications
- Recessed, cast iron, vortex impeller to ensure flow of liquids & solids
- Standard potted epoxy cord seals
- Double mechanical seal
- Continuous duty motor
- Maintenance-free design

**2 Year
Warranty**



Model	HP	Volt	Discharge	Cord Length	Solid Passage	Dimensions (L x W x H)	Weight
VS5A38	.5	115	2"	30'	1.5"	8.7" x 5.7" x 18.3"	41 lbs.
VS5C38	.5	230	2"	30'	1.5"	8.7" x 5.7" x 18.3"	41 lbs.

VS10C59 SEWAGE PUMPS


1 HP Stainless Steel/Cast Iron Sewage Pumps

VS Series

Features and Benefits

- Designed for residential sewage
- Versatile for many solid handling & dewatering applications
- Recessed, cast iron, vortex impeller to ensure flow of liquids & solids
- Standard potted epoxy cord seals
- Double mechanical seal
- Continuous duty motor
- Maintenance-free design

**2 Year
Warranty**



Model	HP	Volt	Discharge*	Cord Length	Solid Passage	Dimensions (L x W x H)	Weight
VS10C59	1	230	2"	30'	1.5"	15.3" x 8.2" x 21.6"	75 lbs.
VS10C59-3	1	230-3ph	2"	30'	1.5"	15.3" x 8.2" x 21.6"	75 lbs.
VS10D59-3	1	460-3ph	2"	30'	1.5"	15.3" x 8.2" x 21.6"	75 lbs.

* 3" discharge available

VS20C75-3 SEWAGE PUMPS


2 HP Stainless Steel/Cast Iron Sewage Pumps

VS Series

Features and Benefits

- Designed for residential sewage
- Versatile for many solid handling & dewatering applications
- Recessed, cast iron, vortex impeller to ensure flow of liquids & solids
- Standard potted epoxy cord seals
- Double mechanical seal
- Continuous duty motor
- Maintenance-free design

**2 Year
Warranty**



Model	HP	Volt	Discharge*	Cord Length	Solid Passage	Dimensions (L x W x H)	Weight
VS20C75-3	2	230-3ph	2"	30'	1.5"	15.3" x 8.2" x 22.4"	77 lbs.
VS20D75-3	2	460-3ph	2"	30'	1.5"	15.3" x 8.2" x 22.4"	77 lbs.

* 3" discharge available

MVGS SERIES GRINDER PUMPS




1 and 2 HP Stainless Steel/Cast Iron Grinder Pumps

Features and Benefits

- Recessed vortex cast iron impeller
- Hardened anti-wear grinding ring and cutter
- Double mechanical seals for better motor protection
- 3450 RPM, 2 pole motor
- Oil filled continuous duty motor
- Potted epoxy cord seal
- Built-in overload protection
- Available with 1.25" flange connection
- Available in prepackaged basin

**2 Year
Warranty**



Model	HP	Volt	Discharge	Cord Length	Dimensions (L x W x H)	Weight
MVGS10CE	1	230	1.25"	20'	16" x 12.5" x 28.5"	88 lbs.
MVGS20CE	2	230	1.25"	20'	16" x 12.5" x 28.5"	88 lbs.

3 phase model available


MVPS SERIES GRINDER PUMPS

Cast Iron Grinder Pumps



Features and Benefits

- All cast iron construction
- Clog free stainless steel rotor and NBR stator
- Hardened, anti-wear grinding ring and cutter
- Double mechanical seal for better motor protection
- 1800 RPM, 4 pole motor
- Oil filled continuous duty motor
- Potted epoxy cord seal
- Built-in overload protection
- Available with 1.25" threaded connection or with rail kit
- Designed for pressure sewer systems
- Available in pre-packaged basin
- Ideal replacement for existing pressure sewer pumps



Model	HP	Volt	Discharge	Cord Length	Dimensions (L x W x H)	Weight
MVPS15CE	1.5	230	1.25"	20'	16" x 12.5" x 28.5"	88 lbs.

3 phase model available


MVPS-RE1 SERIES GRINDER PUMPS

Retrofit Grinder Package



Features and Benefits

- Watertight, 6 pin quick electrical disconnect for E/One® GP200 & GP2000 systems
- Watertight junction box for all electrical connections
- Standard “off the shelf” floats for easy service
- Factory set 100 PSI pressure relief valve
- Anti-siphon protection
- Clog free stainless steel rotor and NBR stator
- Hardened, anti-wear grinding ring and cutter
- Double mechanical seal for better motor protection
- 1800 RPM, 4 pole motor
- Oil filled continuous duty motor
- Potted epoxy cord seal
- Built-in overload protection



HP	Volt	Phase	Amps	RPM	Discharge	Dimensions (L x W x H)	Weight
1.5	230	1	8.0	1750	1.25"	18.75" x 16.75" x 47.25"	100 lbs.

E/One® is a registered trademark of Environmental One Corporation and is not affiliated with Webtrol Pumps


MVGC SERIES GRINDER PUMPS

Cast Iron Grinder Pumps



Features and Benefits

- All cast iron construction
- Recessed vortex cast iron impeller
- Hardened, anti-wear grinding ring and cutter
- Double mechanical seal for better motor protection
- 3PH, 3450 RPM, 2 pole motor
- Oil filled continuous duty motor
- Potted epoxy cord seal
- Available with 2.5" flange connection
- Available in prepackaged basin



Model	HP	Volt	Discharge	Cord Length	Dimensions (L x W x H)	Weight
MVGC30CR	3	230	2.5"	20'	10.8" x 9.5" x 35.8"	179 lbs.
MVGC30DR	3	460	2.5"	20'	10.8" x 9.5" x 35.8"	179 lbs.
MVGC50CR	5	230	2.5"	20'	10.8" x 9.5" x 35.8"	181 lbs.
MVGC50DR	5	460	2.5"	20'	10.8" x 9.5" x 35.8"	181 lbs.
MVGC75CR	7.5	230	2.5"	20'	10.8" x 9.5" x 35.8"	190 lbs.
MVGC75DR	7.5	460	2.5"	20'	10.8" x 9.5" x 35.8"	190 lbs.



There when you need us most


VN SERIES SUBMERSIBLE PUMPS

Non-Clog Wastewater Pumps

VN Series

Features and Benefits

- All cast iron construction
- 3" solids handling
- Single channel, ductile iron impeller
- Double mechanical seal for better motor protection
- 1750 RPM (4 pole motor)
- Oil filled continuous duty motor
- Potted epoxy cord seal
- Available with 4" flange connection
- Available in prepackaged basins



Model	HP	Volt	Phase	Amps	Discharge	Cord Length	Dimensions (L x W x H)	Weight
VN50C49	5	230	3	12.0	4"	20'	25.7" x 15.8" x 32.5"	265 lbs.
VN50D49	5	460	3	6.0	4"	20'	25.7" x 15.8" x 32.5"	265 lbs.
VN75C62	7.5	230	3	18.0	4"	20'	25.7" x 15.8" x 32.5"	267 lbs.
VN75D62	7.5	460	3	9.0	4"	20'	25.7" x 15.8" x 32.5"	267 lbs.
VN100C76	10	230	3	23.0	4"	20'	25.7" x 15.8" x 32.5"	276 lbs.
VN100D76	10	460	3	11.5	4"	20'	25.7" x 15.8" x 32.5"	276 lbs.

All models 60 Hz

WASTEWATER PUMP ACCESSORIES

RAIL KITS

Model	Description	Discharge	Rail Size	Weight
VRK2-2	1 & 2 HP Eff. & Sewage Pump	2"	1"	25 lbs.
VRK2-3	Cast Iron	3"	1"	25 lbs.
GSRK-1.25	304 SS	1.25"	1"	25 lbs.
PSRK-1.25	Ceramic Carbon & Silicon Carbide	1.25"	1"	25 lbs.



GRINDER REPAIR PARTS

Model	Description
MVGS20-IM	Impeller for 1 and 2 HP MVGS Grinder
MVPS15-IM	Stator kit for 1.5 HP MVPS Grinder
MVGS10-CU	Cutter and cutter ring for 1 HP MVGS Grinder
MVGS20-CU	Cutter and cutter ring for 2 HP MVGS Grinder
MVPS15-CU	Cutter and cutter ring for 1.5 HP MVPS Grinder
MVGS20-MS	Mechanical seal for 1 and 2 HP MVGS Grinder
MVGS15-CP	Mechanical seal for 1.5 HP MVPS Grinder
MVGS20-CP	Capacitor kit for 2 HP MVGS Grinder
MVPS15-CP	Capacitor kit for 1.5 HP MVPS Grinder



CONTROL PANEL

Model	Description
W4P23AV3117	Simplex panel for 120/230v pumps up to 17 amps. With pump and alarm disconnect, circuit breaker, weatherproof enclosure and audio/visual alarm and test/silence switch. Comes with 3 10ft. floats. Coil voltage 120v.
Custom configured pump panels available. Please consult factory.	



FIBERGLASS BASINS

Model	Description
FB2472AMVGS	24" x 72" fiberglass basin for MVGS grinder pump assembled with rail, check valves, shut off valves, SS float mounting bracket, SS 1.25" discharge connection and SS 1.5" conduit connection. Includes fiberglass lid and anti float ring.
FB2484AMVPS	24" x 84" fiberglass basin for MVPS grinder pump assembled with rail, check valves, shut off valves, SS float mounting bracket, SS 1.25" discharge connection and SS 1.5" conduit connection. Includes fiberglass lid and anti float ring.
Custom configured pump panels available. Please consult factory.	





Webtrol's Family of Pumps

In addition to quality wastewater pumps, we also offer a full line of industrial and water well pumps.

The Webtrol industrial line includes vertical multistage booster pumps for commercial applications.

Our surface centrifugal and booster pumps include a wide range of self-priming,

corrosion resistant, high head, stainless steel, and cast iron pumps for a variety of industrial, commercial, and agricultural applications.

Our water well line includes 4", 6", 8", and 10" submersible stainless steel pumps.

See our full line of pumps and pump accessories at webtrol.com.



There when you need us most

(314) 631-9200

8417 New Hampshire Ave. | St. Louis, MO 63123
webtrol.com | customerservice@webtrol.com | Fax: (314) 631-3738

WEBTROL is a Division of Weber Industries, Inc.